

RACK-PROTECTOR-X8-1U-PI

SPD - for low voltage / SPD type 3 / For RACK 19"


Multi socket outlet with surge protection SDP Type 3 for rack 19"

visual fault signalling, 3 m power supply cord, industrial plug 16 A 2P+PE


- multiple socket outlet with integrated surge protection SPD Type 3
- for 19" RACK
- for protection of information technology equipments against surge voltage
- mounting height 1U



Product dimensions



Basic circuit diagram



Parameter name	Parameter value	
Type of SPD	T3	
Mounting	19" rack	
Nominal voltage	U_n	230 V AC
Maximum operating voltage	U_c	275.00 V AC
Nominal load current	I_L	16.000 A
Type of network	TN	
Maximum overcurrent protection	16 A gL/gG or C 16 A	
Short-circuit current rating	I_{SCCR}	6.0 kA
Residual current	I_{PE}	0.004 mA
Nominal discharge current (8/20 μ s) L-N	I_n	3.00 kA
Nominal discharge current (8/20 μ s) L+N-PE	I_n	5.00 kA
Nominal discharge current (8/20 μ s) N-PE	I_n	3.00 kA
Test voltage L-N	U_{oc}	6.0 kV
Test voltage N-PE	U_{oc}	6.0 kV
Test voltage L+N-PE	U_{oc}	10.0 kV
Voltage protection level mode L-N	U_p	1.20 kV
Voltage protection level mode L-PE	U_p	1.50 kV

Voltage protection level mode N-PE	U_p	1.50 kV
Response time L-N	t_a	25 ns
Response time N-PE	t_a	100 ns
Fault indication		red indicator
Degree of protection		IP 40
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000942
Customs tariff number		85363010
EAN		8595090562559
Order number		A06255

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu
Technická podpora: 800 818 818 | podpora@saltek.cz

29.03.2025 -
11:47:29