

# RACK-PROTECTOR-EURO-X12-1U-PI

## SPD - for low voltage / SPD type 3 / For RACK 19"


Multi socket outlet with surge protection SPD Type 3 for 19" RACK

visual fault signalling, 3 m power supply cord, industrial plug 16A 2P+PE


- multiple socket outlet with integrated surge protection SPD Type 3
  - mounting height 1U
- for 19" RACK
  - 12x EURO socket outlet
- for protection of information technology equipments against surge voltage



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		T3
Mounting		19" rack
Nominal voltage	$U_n$	230 V AC
Maximum operating voltage	$U_c$	275.00 V AC
Nominal load current	$I_L$	16.000 A
Type of network		TN
Maximum overcurrent protection		16 A gL/gG or C 16 A
Short-circuit current rating	$I_{SCCR}$	6.0 kA
Residual current	$I_{PE}$	0.004 mA
Nominal discharge current (8/20 $\mu$ s) L-N	$I_n$	3.00 kA
Nominal discharge current (8/20 $\mu$ s) L+N-PE	$I_n$	5.00 kA
Nominal discharge current (8/20 $\mu$ s) N-PE	$I_n$	3.00 kA
Test voltage L-N	$U_{oc}$	6.0 kV
Test voltage N-PE	$U_{oc}$	6.0 kV
Test voltage L+N-PE	$U_{oc}$	10.0 kV
Voltage protection level mode L-N	$U_p$	1.20 kV
Voltage protection level mode L-PE	$U_p$	1.50 kV

Voltage protection level mode N-PE	$U_p$	1.50 kV
Response time L-N	$t_a$	25 ns
Response time N-PE	$t_a$	100 ns
Fault indication		red indicator
Degree of protection		IP 20
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000942
Customs tariff number		85363010
EAN		8595090562566
Order number		A06256

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | [info@saltek.cz](mailto:info@saltek.cz) | [www.saltek.eu](http://www.saltek.eu)  
 Technická podpora: 800 818 818 | [podpora@saltek.cz](mailto:podpora@saltek.cz)

22.02.2025 -  
18:45:45