


SLP-275-VB/3+1

SPD - for low voltage / SPD type 2 / Combination type

Combined type surge arrester for three-phase TN-S and TT systems
pluggable module, visual fault signalling

- combination of combined type surge arrester (serial combination varistor+GDT) and encapsulated spark gap, connected in the 3+1 mode
- installation to LV installations, especially to sub-distribution boards in areas with unstable grid voltage and where diesel generators are used, suitable also for measuring circuits
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike in areas with higher storm activity or switching overvoltages or as the first stage of for protection for measuring circuits
- zero leakage current



Parameter name	Parameter value	
Type of SPD	T2	
Mounting	DIN rail 35 mm	
Nominal voltage	U_n	230/400 V AC
Maximum operating voltage L-N	U_c	275.00 V AC
Maximum operating voltage N-PE	U_c	255.00 V AC
Type of network	TT TN-S	
Maximum overcurrent protection	125 A gL/gG	
Short-circuit current rating	I_{SCCR}	50.0 kA
Residual current	I_{PE}	0.002 mA
Nominal discharge current (8/20 μ s)	I_n	20.00 kA
Maximum discharge current (8/20 μ s)	I_{max}	40.00 kA

Voltage protection level mode L-N	U_p	1.50 kV
Voltage protection level mode L-PE	U_p	2.50 kV
Voltage protection level mode N-PE	U_p	1.50 kV
Ability to independently switch off the following current N-PE	I_{fi}	0.1 kA
Response time	t_a	100 ns
TOV 5 s L-N		335 V
TOV characteristic (TOV 5 s)		withstand
TOV 120 min L-N		440 V
TOV characteristic (120 min)		withstand
TOV 200 ms L-PE		1 455 V
TOV 200 ms N-PE		1 200 V
TOV characteristic (TOV 200 ms)		withstand
Cross-section of connected conductors solid (min)		1.00 mm ²
Cross-section of connected conductors solid (max)		35.00 mm ²
Cross-section of connected conductors stranded (min)		1.00 mm ²
Cross-section of connected conductors stranded (max)		25.00 mm ²
Fault indication		red indication field
Remote indication		no
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 80 °C
Humidity		5 - 95 %
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000941
Plug module		SLP-275-VB/0 SLP-NPE V/0
Customs tariff number		85363030
EAN		8595090570592
Order number		A07059