

# FLP-PV275 V/U


## SPD - for DC and PV / SPD PV type 1 / MOV

Lightning current arrester and surge arrester for PV systems  
pluggable module, visual fault signalling, module locking


- varistor lightning current arrester and surge arrester in 'U' connection
- for protection of PV systems on the roofs, where the separating spark-over distance is not kept (connection to LPS)
- maximum continuous operating voltage for PV application:  $UCPV \geq 1.2x$  UOC STC



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		PV T1, PV T2
Mounting		DIN rail 35 mm
Maximum operating voltage mode +/-PE, -/PE	$U_{CPV}$	280.00 V DC
Short-circuit current rating	$I_{SCPV}$	10 000 A DC
Residual current mode +/-PE, -/PE	$I_{PE}$	0.500 mA AC
Residual current mode +/-PE, -/PE	$I_{PE}$	0.020 mA DC
Total discharge current (10/350 $\mu$ s)	$I_{Total(10/350)}$	25.00 kA
Lightning impulse current (10/350 $\mu$ s)	$I_{imp}$	12.50 kA
Total discharge current (8/20 $\mu$ s)	$I_{Total(8/20)}$	120.00 kA
Nominal discharge current (8/20 $\mu$ s)	$I_n$	30.00 kA
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$	60.00 kA
Voltage protection level mode +/-	$U_p$	2.50 kV
Voltage protection level mode +/-PE, -/PE	$U_p$	1.30 kV
Response time	$t_a$	25 ns
Cross-section of connected conductors solid (min)		1.00 mm <sup>2</sup>
Cross-section of connected conductors solid (max)		35.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (min)		1.00 mm <sup>2</sup>

Cross-section of connected conductors stranded (max)	25.00 mm <sup>2</sup>
Fault indication	red indication field
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
According to standard	EN 61643-31, IEC 61643-31
ETIM Class	EC001457
Plug module	FLP-PV275U V/0
Customs tariff number	85363090
EAN	8595090574071
Order number	A07407

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | [info@saltek.cz](mailto:info@saltek.cz) | [www.saltek.eu](http://www.saltek.eu)  
Technická podpora: 800 818 818 | [podpora@saltek.cz](mailto:podpora@saltek.cz)

22.12.2024 -  
10:14:00