

# SLP-075 VB/1 S

## SPD - for low voltage / SPD type 2 / Combination type

Combined type surge arrester for TN and TT systems or signal lines

pluggable module, visual fault signalling, remote fault signalling

- combined type surge arrester (serial combination varistor+GDT)
- installation to LV installations, especially to sub-distribution boards, suitable also for measuring circuits
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike in areas with higher storm activity or switching overvoltages or as the first stage of protection for measuring circuits
- no leakage current



### Product dimensions

### Basic circuit diagram

Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Maximum operating voltage	$U_c$ 75.00 V AC
Maximum operating voltage	$U_c$ 100.00 V DC
Type of network	TN
Maximum overcurrent protection	125 A gL/gG
Short-circuit current rating	$I_{SCCR}$ 35.0 kA
Nominal discharge current (8/20 $\mu$ s)	$I_n$ 15.00 kA
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$ 25.00 kA
Voltage protection level	$U_p$ 0.60 kV
Voltage protection level at 5 kA	$U_p$ 0.30 kV
Response time	$t_a$ 100 ns
Cross-section of connected conductors solid (min)	1.00 mm <sup>2</sup>

Cross-section of connected conductors solid (max)	<b>35.00 mm<sup>2</sup></b>
Cross-section of connected conductors stranded (min)	<b>1.00 mm<sup>2</sup></b>
Cross-section of connected conductors stranded (max)	<b>25.00 mm<sup>2</sup></b>
Cross-section of remote indication conductors solid (max)	<b>1.5 mm<sup>2</sup></b>
Cross-section of remote indication conductors stranded (max)	<b>1.5 mm<sup>2</sup></b>
Fault indication	<b>red indication field</b>
Remote indication	<b>potential-free change-over contact</b>
Remote indication contacts	<b>250V/0,5A AC,250V/0,1A DC</b>
Degree of protection	<b>IP 20</b>
Range of ambient temperatures (min/max)	<b>-40 / 80 °C</b>
Humidity	<b>5 - 95 %</b>
According to standard	<b>EN 61643-11:2012, IEC 61643-11:2011</b>
ETIM Class	<b>EC000941</b>
Plug module	<b>SLP-075 VB/0</b>
Customs tariff number	<b>85363030</b>
EAN	<b>8595090521563</b>
Order number	<b>A02156</b>