

FLP-12,5 V/1


SPD - for low voltage / SPD type 1 / MOV

Lightning current and surge arrester for systems TN and TT
pluggable module, visual fault signalling


- varistor lightning current arrester
- installation at the boundary of zones LPZ 0 and LPZ 1 or higher, for objects in LPL III and IV
- for protection against impact of partial lightning currents, induced overvoltages during a lightning strike or switching overvoltages



Product dimensions



Basic circuit diagram



| Parameter name | Parameter value |
|---|----------------------|
| Type of SPD | T1,T2 |
| Mounting | DIN rail 35 mm |
| Nominal voltage | U_n 230 V AC |
| Maximum operating voltage | U_c 275.00 V AC |
| Maximum operating voltage | U_c 350.00 V DC |
| Type of network | TN |
| Maximum overcurrent protection | 160 A gL/gG |
| Short-circuit current rating | I_{SCCR} 50.0 kA |
| Lightning impulse current (10/350 μ s) | I_{imp} 12.50 kA |
| Nominal discharge current (8/20 μ s) | I_n 30.00 kA |
| Maximum discharge current (8/20 μ s) | I_{max} 60.00 kA |
| Voltage protection level | U_p 1.50 kV |
| Voltage protection level at 5 kA | U_p 0.90 kV |
| Response time | t_a 25 ns |
| TOV 5 s L-N | 335 V |
| TOV characteristic (TOV 5 s) | withstand |
| Cross-section of connected conductors solid (min) | 1.00 mm ² |

| | |
|--|-------------------------------------|
| Cross-section of connected conductors solid (max) | 35.00 mm ² |
| Cross-section of connected conductors stranded (min) | 1.00 mm ² |
| Cross-section of connected conductors stranded (max) | 25.00 mm ² |
| Fault indication | red indication field |
| Degree of protection | IP 20 |
| Range of ambient temperatures (min/max) | -40 / 80 °C |
| Humidity | 5 - 95 % |
| According to standard | EN 61643-11:2012, IEC 61643-11:2011 |
| ETIM Class | EC001457 |
| Plug module | FLP-12,5 V/0 |
| Customs tariff number | 85363090 |
| EAN | 8595090534211 |
| Order number | A03421 |