

FLP-B+C MAXI VS/1

SPD - for low voltage / SPD type 1 / Combination type - T1+T2 (25 kA)


Combination of lightning current and surge arrester for systems TN and TT

pluggable module, visual fault signalling, module locking, remote fault signalling


- high performance lightning current arrester
- installation at the boundary of zones LPZ 0 and LPZ 1 or higher, mainly to main distribution boards
- for protection against impact of direct or indirect lightning strikes in wide range of applications – houses, office or industrial buildings, resp. to sub-distribution boards in large buildings



Product dimensions



Basic circuit diagram



Parameter name	Parameter value
Type of SPD	T1,T2
Mounting	DIN rail 35 mm
Nominal voltage	U_n 230 V AC
Maximum operating voltage	U_c 260.00 V AC
Nominal load current for "V" connection	I_L 125 A
Type of network	TN
Maximum overcurrent protection	250 A gL/gG
Maximum overcurrent protection for "V" connection	125 A gL/gG
Short-circuit current rating	I_{SCCR} 50.0 kA
Lightning impulse current (10/350 μ s)	I_{imp} 25.00 kA
Nominal discharge current (8/20 μ s)	I_n 30.00 kA
Maximum discharge current (8/20 μ s)	I_{max} 60.00 kA
Voltage protection level	U_p 1.50 kV
Residual voltage of MOV at I_n	U_{RES} 0.85 kV
Response time	t_a 100 ns
TOV 5 s L-N	335 V

TOV characteristic (TOV 5 s)	withstand
TOV 120 min L-N	440 V
TOV characteristic (120 min)	withstand
Cross-section of connected conductors solid (min)	2.50 mm²
Cross-section of connected conductors solid (max)	50.00 mm²
Cross-section of connected conductors stranded (min)	2.50 mm²
Cross-section of connected conductors stranded (max)	35.00 mm²
Cross-section of remote indication conductors solid (max)	1.5 mm²
Cross-section of remote indication conductors stranded (max)	1.5 mm²
Fault indication	red indication field
Remote indication	potential-free change-over contact
Remote indication contacts	250V/0,5A AC,250V/0,1A DC
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-11:2012, IEC 61643-11:2011
ETIM Class	EC001457
Plug module	FLP-B+C MAXI V/0
Customs tariff number	85363090
EAN	8595090535331
Order number	A03533