


DS-V130-RS

SPD - for data, signalling and telecommunications lines / I&C / Single stage SPD (DS)


Single stage surge arrester – Varistor

V – Varistor, screw terminals

- single stage surge arrester
- installation close to protected equipment
- for protection of signaling, data and other lines against impact of surge voltage




Product dimensions



*1 – šifra svorky bez víčka
** – šifra svorky s víčkem

Basic circuit diagram



Parameter name	Parameter value
Type of SPD	C2
Location of SPD	ST 2
Mounting	DIN rail 35 mm
Maximum operating voltage U_C	140.00 V AC
Maximum operating voltage U_C	180.00 V DC
Nominal load current I_L	16.000 A
C2 nominal discharge current (8/20 μ s) per core I_n	6.00 kA
C2 voltage protection level mode core-PE at I_n U_p	530.00 V
Response time core-PE t_a	25 ns
Connection (input - output)	terminals-terminals
Cross-section of connected conductors solid (min)	0.14 mm²
Cross-section of connected conductors solid (max)	4.00 mm²
Cross-section of connected conductors stranded (min)	0.14 mm²
Cross-section of connected conductors stranded (max)	2.50 mm²
Range of ambient temperatures (min/max)	-40 / 70 °C

According to standard	EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class	EC000943
Customs tariff number	85363010
EAN	8595090551515
Order number	A05151

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu

Technická podpora: 800 818 818 | podpora@saltek.cz

10.05.2026 -
00:52:25