


# ISGO-500H Ex

## ISG - Isolating spark gaps / Ex environment


Isolation spark gap for Ex areas

connecting cable and M8 bolt with nut, stainless steel enclosure


- heavy duty encapsulated isolating spark gap for use in Hazardous (Ex) Areas II 2G Ex mb IIC T6 Gb and II 2D Ex mb IIIC T80 °C Db
- for indirect connection (earthing) of isolated conductive parts under lightning conditions
- for safe installation in Ex zone 1 (gas) or 21 (dust)



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Classification		class H - heavy duty
Isolation resistance		100.00 MOhm
Lightning impulse current	$I_{imp}$	100.00 kA
Rated impulse sparkover voltage	$U_{imp}$	1.50 kV
Rated power frequency withstand voltage	$U_{WAC}$	0.350 kV
Rated DC withstand voltage	$U_{WDC}$	0.500 kV
Degree of protection		IP 67
Range of ambient temperatures (min/max)		-40 / 50 °C
According to standard		EN 62561-3, EN 60079-0, EN 60079-18
Explosion-tested version		II 2G Ex mb IIC T6 Gb, II 2D Ex mb IIIC T80°C Db
ETIM Class		EC000510
Customs tariff number		85363090
EAN		8595090555148
Order number		A05514

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | [info@saltek.cz](mailto:info@saltek.cz) |  
[www.saltek.eu](http://www.saltek.eu)  
*Technická podpora: 800 818 818 | [podpora@saltek.cz](mailto:podpora@saltek.cz)*

01.04.2025 -  
16:43:48