

DMLF-024/1-RB

SPD - for data, signalling and telecommunications lines / I&C / Specials - RFI filter


Surge protection for low-frequency 2-core signalling networks

coupling impedance (inductance), screwless terminals


- coarse and fine surge protection for low-frequency 2-core signalling networks
- installation close to protected equipment
- for protection of analogue measuring lines in the areas with RF disturbance
- coarse and fine surge protection in differential mode (core – core) and common mode (core – PE)



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		C2
Location of SPD		ST 2
Mounting		DIN rail 35 mm
Nominal voltage	U_n	24 V DC
Maximum operating voltage	U_c	31.00 V DC
Nominal load current	I_L	0.100 A
Threshold frequency core-core	f	0.07 MHz
D1 impulse discharge current (10/350 μ s) per core	I_{imp}	0.50 kA
D1 total discharge current (10/350 μ s) cores-PE	I_{Total}	1.00 kA
C2 nominal discharge current (8/20 μ s) per core	I_n	5.00 kA
C2 total discharge current (8/20 μ s) cores-PE	I_{Total}	10.00 kA
C2 voltage protection level mode core-PE at I_n	U_p	80 V

C2 voltage protection level mode core-core at In	U_p	65 V
C3 voltage protection level mode core-PE at 1 kV/ μ s	U_p	55 V
C3 voltage protection level mode core-core at 1 kV/ μ s	U_p	55 V
Response time core-core	t_a	25 ns
Response time core-PE	t_a	25 ns
Connection (input - output)	screwless terminals/screwless terminals	
Cross-section of connected conductors solid (min)	0.08 mm ²	
Cross-section of connected conductors solid (max)	4.00 mm ²	
Cross-section of connected conductors stranded (min)	0.08 mm ²	
Cross-section of connected conductors stranded (max)	2.50 mm ²	
Degree of protection	IP 20	
Range of ambient temperatures (min/max)	-40 / 70 °C	
According to standard	EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012	
ETIM Class	EC001625	
Customs tariff number	85363010	
EAN	8595090560692	
Order number	A06069	