

# HX 350-N50 F/F

## SPD - for data, signalling and telecommunications lines / Coaxial lines / ST1 (HX)


Lightning current arrester for coaxial lines (antennas)

N connectors, 50 Ohm


- lightning current arrester for coaxial line
- installation at the boundary of LPZ 0 and LPZ 1 zones at the line entry into building
- for protection of telecommunication equipment against impact of direct or indirect lightning strike
- suitable for the combined signal and power supply distribution



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		D1,C2
Location of SPD		ST 1+2
Maximum operating voltage	$U_C$	250.00 V DC
Nominal load current	$I_L$	6.000 A
Frequency range	$f$	0,00 - 3500,00 MHz
Impedance	$Z$	50 $\Omega$
Power (CW)	$P$	570.00 W
Insertion loss typ. (max.)	$A$	0,2 (0,4) dB
VSWR typ. (max.)	VSWR	1,1 (1,2)
D1 impulse discharge current (10/350 $\mu$ s) core-PE	$I_{imp}$	2.50 kA
C2 nominal discharge current (8/20 $\mu$ s) core-PE	$I_n$	10.00 kA
Dynamic spark-over voltage at 1kV/ $\mu$ s	$U_{dyn}$	900.00 V
Response time core-PE	$t_a$	100 ns

Connection (input - output)	N 50
Degree of protection	IP 66
According to standard	EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class	EC001466
Customs tariff number	85363010
EAN	8595090567035
Order number	A06703

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | [info@saltek.cz](mailto:info@saltek.cz) | [www.saltek.eu](http://www.saltek.eu)

Technická podpora: 800 818 818 | [podpora@saltek.cz](mailto:podpora@saltek.cz)

22.12.2024 -  
14:06:25